

AT-CWP Series
Cutoff Style Wall Pack



Desc: Full Cutoff LED Wall Pack Fixture

Details

Constructed of die cast aluminum with powder coat finish and glass lens, this fixture is sealed to resist water, dust and insects. Meanwell brand driver emits constant current to high output CREE LED chips for maximum efficiency. The heatsink is a lightweight design which efficiently transfers thermal load to the external housing. Hardware is stainless steel.

Approvals

UL, DLC, FCC, ROHS

Power Consumption

30w, 60w, 100w

Input Voltage

120-277VAC

Dimming Options

Not dimmable

Lumen Output

5900, 8900, 12900

Features

Energy efficient: save up to 80% in energy costs
 High lumen output
 Mercury free
 Instant-on at 100%

Warranty

3 years

Applications

Retail and commercial, education, government, industrial

Ordering Information

Sample #: AT-OWP-90W-40

| Series | Style/Size | Color Temp | | |
|--------|----------------|------------|--|--|
| AT-OWP | 60W- 60 watt | 40- 4000K | | |
| | 90W- 90 watt | 50- 5000K | | |
| | 100W- 100 watt | | | |

Caution: Risk of electric shock. Do not open. No user serviceable parts inside. Turn off power before inspection, installation or removal. Ensure that all batteries and capacitors have been discharged.

<http://www accuratetechinc.com>

**AT-CWP
Data Sheet**



PHYSICAL DATA

DIMENSIONS

| BASE | FINISH | DIAMETER (IN) | LENGTH (IN) | WIDTH (IN) | HEIGHT (IN) |
|-------------|--------|---------------|-------------|------------|-------------|
| AT-CWP-30w | BZ | | 14.2 | 11.4 | 9 |
| AT-CWP-60w | BZ | | 14.2 | 11.4 | 9 |
| AT-CWP-100w | BZ | | 18.2 | 13.8 | 9 |

ELECTRICAL DATA

| | POWER (W) | MAX. INPUT (V) | CONTROL | POWER FACTOR |
|-------------|-----------|----------------|---------|--------------|
| AT-CWP-30w | 30 | 120-277 | S | 0.98 |
| AT-CWP-60w | 60 | 120-277 | S | 0.98 |
| AT-CWP-100w | 100 | 120-277 | S | 0.98 |

LIGHTING DATA

| | FLUX (LM) | EFFICACY (LM/W) | BEAM ANGLE | CRI | EQUIVALENT |
|-------------|-----------|-----------------|------------|-----|------------|
| AT-CWP-30w | 2900 | 96.7 | 120 | >75 | 100W HID |
| AT-CWP-60w | 5900 | 98.3 | 120 | >75 | 175W HID |
| AT-CWP-100w | 9500 | 98.9 | 120 | >75 | 250W HID |

SAFETY & LEGAL DATA

| | WEATHER RATING | UL | DLC | ENERGY STAR | WARRANTY (YRS) |
|-------------|----------------|----|-----|-------------|----------------|
| AT-CWP-30w | WET LOC. | X | | | 3 |
| AT-CWP-60w | WET LOC. | X | | | 3 |
| AT-CWP-100w | WET LOC. | X | | | 3 |

Caution: Risk of electric shock. Do not open. No user serviceable parts inside.
Turn off power before inspection, installation or removal. Ensure that all batteries and capacitors have been discharged.

<http://www.accuratetechinc.com>