

AT-PNL Series
LED Grid Mount Panel Light



Desc: LED Ceiling Panel Light Fixture

Details

AT-PNL series LED ceiling panel lights are suitable for new construction or direct replacement of existing linear fluorescent lay-in troffers. Panel lights provide even, reliable consistent light with no glare or flicker. Available in multiple color temperatures to match existing lighting. Thin and lightweight, panels are easy to install.

Approvals

UL, DLC, ROHS, FCC

Power Consumption

40w (2x2), 75W (2x4)

Input Voltage

120-277w

Dimming Options

0-10v dimming

Lumen Output

3600 (2x2) 6750 (2x4)

Features

- Energy efficient: save up to 70% in energy costs
- High lumen output
- Mercury free
- Instant-on at 100%

Warranty

5 year

Applications

Retail and commercial, education, government, industrial

Ordering Information

Sample #: AT-PNL-2x4-40

Series	Style/Size	Color Temp		
AT-PNL-	2x2-	30- 3000K		
	2x4-	40- 4000K		
		50- 5000K		

Caution: Risk of electric shock. Do not open. No user serviceable parts inside. Turn off power before inspection, installation or removal. Ensure that all batteries and capacitors have been discharged.

<http://www accuratetechinc.com>

AT-PNL
Data Sheet



PHYSICAL DATA					
		DIMENSIONS			
BASE	FINISH	DIAMETER (IN)	LENGTH (IN)	WIDTH (IN)	HEIGHT (IN)
2x2	S		23.6	23.6	0.47
2x4	S		47.24	23.6	0.47

ELECTRICAL DATA				
	POWER (W)	MAX. INPUT (V)	CONTROL	POWER FACTOR
2x2	40	100-277	D	
2x4	75	100-277	D	

LIGHTING DATA					
	FLUX (LM)	EFFICACY (LM/W)	BEAM ANGLE	CRI	EQUIVALENT
2x2	3600	90	180	>80	2X 32W T8
2x4	6750	71	180	>80	4X 32W T8

SAFETY & LEGAL DATA					
	WEATHER RATING	UL	DLC	ENERGY STAR	WARRANTY (YRS)
2x2		X	X		5
2x4		X	X		5

Caution: Risk of electric shock. Do not open. No user serviceable parts inside.
Turn off power before inspection, installation or removal. Ensure that all batteries and capacitors have been discharged.

<http://www.accuratetechinc.com>